

Intel® C++ Compiler Professional Edition 11.1 for Linux* Installation Guide and Release Notes

Document number: 321412-002US
12 August 2010

Table of Contents

1	Introduction	5
1.1	Change History	5
1.2	Product Contents	6
1.3	System Requirements.....	6
1.3.1	Red Hat Enterprise Linux* 3, SUSE LINUX Enterprise Server* 9 Support Deprecated	8
1.3.2	Cluster OpenMP* Libraries and Command Line Options Deprecated	9
1.4	Documentation.....	9
1.5	Japanese Language Support	9
1.6	Technical Support.....	9
2	Installation.....	9
2.1.1	Silent Install	10
2.1.2	Eclipse* Integration Installation	10
2.1.3	Known Installation Issues	10
2.2	Installation Folders.....	11
2.3	Removal/Uninstall	12
3	Intel® C++ Compiler	12
3.1	Compatibility	13
3.2	New and Changed Features	13
3.3	New and Changed Compiler Options.....	13
3.3.1	-O0 no longer implies -mp	13
3.4	Other Changes	13
3.4.1	Optimization Reports Disabled by Default.....	13
3.4.2	Establishing the Compiler Environment.....	13

3.4.3	Instruction Set Default Changed to Require Intel® Streaming SIMD Extensions 2 (Intel® SSE2).....	14
3.4.4	OpenMP* Libraries Default to “compat”.....	14
3.4.5	<code>mathf.h</code> No Longer Provided.....	14
3.4.6	Sampling-based Profile Guided Optimization Feature Removed.....	14
3.4.7	OpenMP Header File Changed.....	15
3.5	Using Source Checker in the Eclipse* IDE.....	15
3.6	Known Issues.....	16
3.6.1	TR1 System Headers.....	16
3.6.2	The default behavior for <code>KMP_AFFINITY</code> has changed.....	16
3.6.3	Fatal error from old version of <code>ld</code>	16
3.6.4	Certain Intel® AVX Architecture Instructions and Intrinsics Removed.....	16
4	Intel® Debugger (IDB).....	17
4.1	Setting up the Java Runtime Environment.....	17
4.2	Starting the Debugger.....	17
4.3	Additional Documentation.....	17
4.4	Debugger Features.....	18
4.4.1	Main Features of IDB.....	18
4.4.2	New and Changed Features.....	18
4.5	Known Problems.....	18
4.5.1	Data Sharing Detection Issues.....	18
4.5.2	Signals Dialog not working.....	18
4.5.3	Break on Re-entrant Call not Supported.....	18
4.5.4	Resizing GUI.....	18
4.5.5	Kill Process.....	19
4.5.6	Decimal Floating Point Not Supported.....	19
4.5.7	<code>\$cdir</code> , <code>\$cwd</code> Directories.....	19
4.5.8	<code>info stack</code> Usage.....	19
4.5.9	<code>\$stepg0</code> Default Value Changed.....	19
4.5.10	SIGTRAP error on some Linux* Systems.....	19
4.5.11	<code>idb</code> GUI cannot be used to debug MPI processes.....	19
5	Eclipse Integration.....	20
5.1	Supplied Integrations.....	20

5.1.1	Eclipse 3.5 and CDT 6.0	20
5.1.2	Eclipse 3.4 and CDT 5.0	20
5.1.3	Integration notes	20
5.2	How to Install the Intel C++ Eclipse Product Extension in Your Eclipse Platform	20
5.2.1	Eclipse 3.5.0 and CDT 6.0.0 “Galileo”	21
5.2.2	Eclipse 3.4.0 and CDT 5.0.0 “Ganymede”	21
5.3	How to Obtain and Install Eclipse, CDT and a JRE	22
5.3.1	Eclipse 3.5.0 with CDT 6.0.0	22
5.3.2	Eclipse 3.4.0 and CDT 5.0.0	22
5.3.3	Installing JRE, Eclipse and CDT	22
5.4	Launching Eclipse for Development with the Intel C++ Compiler	23
5.5	Installing on Fedora* Systems	23
5.6	Selecting Compiler Versions	24
6	Intel® Integrated Performance Primitives	24
6.1	New and Changed Features	24
6.1.1	Intel® Integrated Performance Primitives 6.1 Update 5	24
6.1.2	Intel® Integrated Performance Primitives 6.1 Update 4	24
6.1.3	Intel® Integrated Performance Primitives 6.1 Update 3	24
6.1.4	Intel® Integrated Performance Primitives 6.1 Update 2	24
6.2	Known Limitations	25
6.3	Intel® IPP Cryptography Libraries are Available as a Separate Download	25
6.4	Intel® IPP Code Samples	25
7	Intel® Math Kernel Library	25
7.1	Changes in This Version	25
7.1.1	Intel® Math Kernel Library 10.2 Update 6	25
7.1.2	Intel® Math Kernel Library 10.2 Update 5	26
7.1.3	Intel® Math Kernel Library 10.2 Update 4	27
7.1.4	Intel® Math Kernel Library 10.2 Update 3	27
7.1.5	Intel® Math Kernel Library 10.2 Update 2	28
7.2	Known Issues	30
7.3	Notices	30
7.4	Attributions	31
8	Intel® Threading Building Blocks	31

8.1	Changes in This Version	31
8.1.1	Intel® Threading Building Blocks 2.2 Update 2	31
8.1.2	Intel® Threading Building Blocks 2.2 Update 1	32
8.2	Known Issues	32
9	Disclaimer and Legal Information	33

1 Introduction

This document describes how to install the product, provides a summary of new and changed features and includes notes about features and problems not described in the product documentation.

1.1 Change History

This section highlights important changes in product updates. For a list of corrections to reported problems, please read [Intel® Professional Edition Compilers 11.1 Fixes List](#), [Intel® IPP Library 6.1 Fixes List](#), [Intel® Math Kernel Library 10.2 Fixes List](#) and [Intel® Threading Building Blocks 2.2 Changes](#).

Update 7

- [Intel® Math Kernel Library updated](#) to 10.2 Update 6
- Added support for SUSE LINUX Enterprise Server* 11 SP1
- Corrections to reported problems

Update 6

- [Intel® Integrated Performance Primitives updated](#) to 6.1 Update 5
- [Intel® Math Kernel Library updated](#) to 10.2 Update 5
- Corrections to reported problems

Update 5 (11.1.069)

- [Intel® Integrated Performance Primitives updated](#) to 6.1 Update 4
- [Intel® Math Kernel Library updated](#) to 10.2 Update 4
- [Intel® Threading Building Blocks updated](#) to 2.2 Update 2
- Note added about [Cluster OpenMP* libraries removed in future version](#)
- Corrections to reported problems

Update 4 (11.1.064)

- [OpenMP header file changed](#) to improve error detection
- [Intel® Math Kernel Library updated](#) to 10.2 Update 3
- [Intel® Integrated Performance Primitives updated](#) to 6.1 Update 3
- Corrections to reported problems

Update 3 (11.1.059)

- [Intel® Threading Building Blocks updated](#) to 2.2 Update 1
- Corrections to reported problems

Update 2 (11.1.056)

- Ubuntu* 9.04 now supported
- Note added about [non-RPM install forced on Fedora* 10](#).

- Note added about [new options](#) `-mkl` and `-xAVX`
- Note added about [removal of certain Intel® AVX architecture instructions and intrinsics](#)
- Full support for Eclipse* CDT 6.0 is now available
- Corrections to reported problems

Update 1 (11.1.046)

- Note added about [change in behavior of `-O0`](#)
- Partial support for Eclipse CDT 6.0 added
- Corrections to reported problems

1.2 Product Contents

*Intel® C++ Compiler Professional Edition 11.1 for Linux** includes the following components:

- Intel® C++ Compilers for building applications that run on IA-32, Intel® 64 and IA-64 architecture systems running the Linux* operating system
- Intel® Debugger
- Intel® Assembler for IA-64 architecture applications
- Intel® Integrated Performance Primitives 6.1 Update 5
- Intel® Math Kernel Library 10.2 Update 6
- Intel® Threading Building Blocks 2.2 Update 2
- Integration into the Eclipse* development environment
- On-disk documentation

1.3 System Requirements

For an explanation of architecture names, see <http://software.intel.com/en-us/articles/intel-architecture-platform-terminology/>

Requirements to develop IA-32 architecture applications

- A PC based on an IA-32 or Intel® 64 architecture processor supporting the Intel® Streaming SIMD Extensions 2 (Intel® SSE2) instructions (Intel® Pentium® 4 processor or later, or compatible non-Intel processor)
 - Development for a target different from the host may require optional library components to be installed from your Linux Distribution.
 - For the best experience, a multi-core or multi-processor system is recommended
- 1GB of RAM (2GB recommended)
- 3GB free disk space for all features
- One of the following Linux distributions (this is the list of distributions tested by Intel; other distributions may or may not work and are not recommended - please refer to the [Technical Support](#) section if you have questions):
 - Asianux* 3.0
 - Debian* 4.0
 - Fedora* 10
 - Red Hat Enterprise Linux* 3, 4, 5

- SUSE LINUX Enterprise Server* 9, 10, 11, 11 SP1
- TurboLinux* 11
- Ubuntu* 9.04
- Linux Developer tools component installed, including gcc, g++ and related tools
- binutils 2.17.50 or later
- Linux component compat-libstdc++ providing libstdc++.so.5
- If developing on an Intel® 64 architecture system, some Linux distributions may require installation of one or more of the following additional Linux components: ia32-libs, lib32gcc1, lib32stdc++6, libc6-dev-i386, gcc-multilib

Requirements to Develop Intel® 64 Architecture Applications

- A PC based on an Intel® 64 architecture processor (Intel® Pentium 4 processor or later, or compatible non-Intel processor)
 - For the best experience, a multi-core or multi-processor system is recommended
- 1GB of RAM (2GB recommended)
- 3GB free disk space for all features
- 100 MB of hard disk space for the virtual memory paging file. Be sure to use at least the minimum amount of virtual memory recommended for the installed distribution of Linux
- One of the following Linux distributions (this is the list of distributions tested by Intel; other distributions may or may not work and are not recommended - please refer to the [Technical Support](#) section if you have questions):
 - Asianux* 3.0
 - Debian* 4.0
 - Fedora* 10
 - Red Hat Enterprise Linux* 3, 4, 5
 - SUSE LINUX Enterprise Server* 9, 10, 11, 11 SP1
 - TurboLinux* 11
 - Ubuntu* 9.04
- Linux Developer tools component installed, including gcc, g++ and related tools
- binutils 2.17.50 or later
- Linux component compat-libstdc++ providing libstdc++.so.5
- Linux component containing 32-bit libraries (may be called ia32-libs)

Requirements to Develop IA-64 Architecture Applications

- A system based on an IA-64 architecture processor (Intel® Itanium®)
- 1GB of RAM (2 GB recommended).
- 3GB free disk space for all features
- One of the following Linux distributions (this is the list of distributions tested by Intel; other distributions may or may not work and are not recommended - please refer to the [Technical Support](#) section if you have questions):
 - Asianux* 3.0
 - Debian* 4.0
 - Red Hat Enterprise Linux* 3, 4, 5

- SUSE LINUX Enterprise Server* 9, 10, 11, 11 SP1
- TurboLinux* 11
- Ubuntu* 9.04
- Linux Developer tools component installed, including gcc, g++ and related tools
- binutils 2.17.50 or later
- Linux component compat-libstdc++ providing libstdc++.so.5

Additional Requirements to use the Graphical User Interface of the Intel® Debugger

- IA-32 architecture system or Intel® 64 architecture system
- Java* Runtime Environment (JRE) 5.0 (also called 1.5) or 6.0 (1.6)
 - A 32-bit JRE must be used on an IA-32 architecture system and a 64-bit JRE must be used on an Intel® 64 architecture system

Additional Requirements to use Eclipse* Integration

- IA-32 architecture system or Intel® 64 architecture system
- Eclipse* 3.5.x or 3.4.x
- Eclipse C/C++ Development Tools (CDT) 6.0.x or 5.0.x
- Java Run-Time Environment 5.0 (1.5) or 6.0 (1.6)

Notes

- The Intel compilers are tested with a number of different Linux distributions, with different versions of gcc. Some Linux distributions may contain header files different from those we have tested, which may cause problems. The version of glibc you use must be consistent with the version of gcc in use. For best results, use only the gcc versions as supplied with distributions listed above.
- Compiling very large source files (several thousands of lines) using advanced optimizations such as `-O3`, `-ipo` and `-openmp`, may require substantially larger amounts of RAM.
- The above lists of processor model names are not exhaustive - other processor models correctly supporting the same instruction set as those listed are expected to work. Please refer to the *Technical Support* section if you have questions regarding a specific processor model
- Some optimization options have restrictions regarding the processor type on which the application is run. Please see the documentation of these options for more information.

1.3.1 Red Hat Enterprise Linux* 3, SUSE LINUX Enterprise Server* 9 Support Deprecated

In a future major release of Intel C++ Compiler, support will be removed for installation and use on Red Hat Enterprise Linux 3 and SUSE LINUX Enterprise Server 9. Intel recommends migrating to a newer version of these operating systems.

1.3.2 Cluster OpenMP* Libraries and Command Line Options Deprecated

The Cluster OpenMP* feature, available as an unsupported option from whatif.intel.com, depends on libraries and command line support in the compiler product. These libraries and the command line support will be removed from the next major release of the compiler, at which point the Cluster OpenMP feature will no longer be available for use.

1.4 Documentation

Product documentation can be found in the `Documentation` folder as shown under [Installation Folders](#).

1.5 Japanese Language Support

Intel compilers provide support for Japanese language users. Error messages, visual development environment dialogs and some documentation are provided in Japanese in addition to English. By default, the language of error messages and dialogs matches that of your operating system language selection. Japanese-language documentation can be found in the `ja_JP` subdirectory for documentation and samples.

If you wish to use Japanese-language support on an English-language operating system, or English-language support on a Japanese-language operating system, you will find instructions at <http://software.intel.com/en-us/articles/changing-language-setting-to-see-english-on-a-japanese-os-environment-or-vice-versa-on-linux/>

1.6 Technical Support

Register your license at the [Intel® Software Development Products Registration Center](#). Registration entitles you to free technical support, product updates and upgrades for the duration of the support term.

For information about how to find Technical Support, Product Updates, User Forums, FAQs, tips and tricks, and other support information, please visit:

<http://www.intel.com/software/products/support/>

Note: If your distributor provides technical support for this product, please contact them for support rather than Intel.

2 Installation

If you are installing the product for the first time, please be sure to have the product serial number available as you will be asked for it during installation. A valid license is required for installation and use.

If you received your product on DVD, mount the DVD, change the directory (`cd`) to the top-level directory of the mounted DVD and begin the installation using the command:

```
./install.sh
```

If you received the product as a downloadable file, first unpack it into a writeable directory of your choice using the command:

```
tar -xzvf name-of-downloaded-file
```

Then change the directory (`cd`) to the directory containing the unpacked files and begin the installation using the command:

```
./install.sh
```

Follow the prompts to complete installation.

2.1.1 Silent Install

For information on automated or “silent” install capability, please see <http://software.intel.com/en-us/articles/intel-compilers-for-linux-version-111-silent-installation-guide/>

2.1.2 Eclipse* Integration Installation

Please refer to the [section below on Eclipse Integration](#)

2.1.3 Known Installation Issues

- If you have enabled the Security-Enhanced Linux (SELinux) feature of your Linux distribution, you must change the `SELINUX` mode to `permissive` before installing the Intel C++ Compiler. Please see the documentation for your Linux distribution for details. After installation is complete, you may reset the `SELINUX` mode to its previous value.
- On some versions of Linux, auto-mounted devices do not have the "exec" permission and therefore running the installation script directly from the DVD will result in an error such as:

```
bash: ./install.sh: /bin/bash: bad interpreter: Permission denied
```

If you see this error, remount the DVD with `exec` permission, for example:

```
mount /media/<dvd_label> -o remount,exec
```

and then try the installation again.

- On Fedora* 10 systems, the compiler forces a non-RPM install because some versions of Fedora 10 contain a defective `rpm` utility that prevents the Intel® compiler from installing properly.
- The version 11.1 product is fully supported on Ubuntu 9.04 IA-32 and Intel® 64 architecture systems. Due to a restriction in the licensing software, however, it is not possible to use the Trial License feature when evaluating IA-32 components on an Intel® 64 architecture system with Ubuntu 9.04. Earlier versions of Ubuntu, not officially supported by this release of software, may have similar problems. This affects using a Trial License only. Use of serial numbers, license files, floating licenses or other license manager operations, and off-line activation (with serial numbers) is not affected. If you

need to evaluate IA-32 components of the version 11.1 product on an Intel® 64 architecture Ubuntu system, please visit the Intel Software Evaluation Center (<http://www.intel.com/cd/software/products/asm-na/eng/download/eval/>) to obtain an evaluation serial number.

2.2 Installation Folders

The arrangement of installation folders is shown in the diagram below. Not all folders will be present in a given installation.

- <install-dir>/Compiler/11.1/xxx/
 - o bin
 - ia32
 - intel64
 - ia64
 - o include
 - ia32
 - intel64
 - ia64
 - o perf_headers
 - o substitute_headers
 - o lib
 - ia32
 - intel64
 - ia64
 - o eclipse_support
 - o idb
 - eclipse_support
 - gui
 - ia32
 - ia64
 - intel64
 - lib
 - third_party
 - o ipp
 - em64t
 - ia32
 - ia64
 - o mkl
 - benchmarks
 - examples
 - include
 - interfaces
 - lib
 - tests

- tools
- tbb
 - bin
 - em64t
 - examples
 - ia32
 - include
 - itanium
 - lib
- Documentation
- man
- Samples

Where `<install-dir>` is the installation directory (default for system-wide installation is `/opt/intel`) and `xxx` is the three-digit build number and the folders under `bin`, `include` and `lib` are used as follows:

- `ia32`: Files used to build applications that run on IA-32
- `intel64`: Files used to build applications that run on Intel® 64
- `ia64`: Files used to build applications that run on IA-64

If you have both the Intel C++ and Intel Fortran compilers installed, they will share folders for a given version.

2.3 Removal/Uninstall

Removing (uninstalling) the product should be done by the same user who installed it (root or a non-root user). If `sudo` was used to install, it must be used to uninstall as well. It is not possible to remove the compiler while leaving any of the performance library or Eclipse* integration components installed.

1. Open a terminal window and set default (`cd`) to any folder outside `<install-dir>`
2. Type the command: `<install-dir>/bin/ia32/uninstall_cproc.sh` (substitute `intel64` or `ia64` for `ia32` as desired)
3. Follow the prompts
4. Repeat steps 2 and 3 to remove additional platforms or versions

If you have the same-numbered version of Intel® Fortran Compiler installed, it may also be removed. If you have added the Intel C++ Eclipse integration to an instance of Eclipse in your environment, you will need to update your Eclipse configuration by removing the Intel integration extension site from your Eclipse configuration.

3 Intel® C++ Compiler

This section summarizes changes, new features and late-breaking news about the Intel C++ Compiler.

3.1 Compatibility

In version 11.0, the IA-32 architecture default for code generation changed to assume that Intel® Streaming SIMD Extensions 2 (Intel® SSE2) instructions are supported by the processor on which the application is run. [See below](#) for more information.

3.2 New and Changed Features

Please refer to the compiler documentation for details

- Additional features from C++0x
- C++ lambda functions
- Language extensions for parallel execution
- Asynchronous I/O extensions
- Decimal floating point
- `#pragma vector_nontemporal`
- `#pragma unroll_and_jam`
- valarray implementation using IPP option

3.3 New and Changed Compiler Options

- `-diag-enable sc-include`
- `-diag-enable sc-parallel`
- `-mkl[=lib]`
- `-xAVX`

For a list of deprecated compiler options, see the Compiler Options section of the documentation.

3.3.1 `-O0` no longer implies `-mp`

In version 11.1, the `-O0` option for disabling optimizations no longer implies `-mp` for maximizing floating-point precision. The `-mp` switch is deprecated; Intel recommends using an explicit `-fp-model` option for applications that are sensitive to floating-point precision changes.

3.4 Other Changes

3.4.1 Optimization Reports Disabled by Default

As of version 11.1, the compiler no longer issues, by default, optimization report messages regarding vectorization, automatic parallelization and OpenMP threaded loops. If you wish to see these messages you must request them by specifying `-diag-enable vec`, `-diag-enable par` and/or `-diag-enable openmp`, or by using `-vec-report`, `-par-report` and/or `-openmp-report`.

Also, as of version 11.1, optimization report messages are sent to `stderr` and not `stdout`.

3.4.2 Establishing the Compiler Environment

The `iccvars.sh` (`iccvars.csh`) script, used to set up the command-line build environment, has changed. In previous versions, you chose the target platform by selecting either the `cc` or

cce directory root. In version 11.x, there is one version of these scripts and they now take an argument to select the target platform.

The command takes the form:

```
source <install-dir>/Compiler/11.1/xxx/bin/iccvars.sh argument
```

Where `<install-dir>` is the installation directory (default for system-wide installation is `/opt/intel`) and `xxx` is the build number and `argument` is one of `ia32`, `intel64`, `ia64` as described above under [Installation Folders](#). Establishing the compiler environment also establishes the Intel® Debugger (idb) environment.

3.4.3 Instruction Set Default Changed to Require Intel® Streaming SIMD Extensions 2 (Intel® SSE2)

When compiling for the IA-32 architecture, `-msse2` (formerly `-xw`) is the default as of version 11.0. Programs built with `-msse2` in effect require that they be run on a processor that supports the Intel® Streaming SIMD Extensions 2 (Intel® SSE2), such as the Intel® Pentium® 4 processor and some non-Intel processors. No run-time check is made to ensure compatibility – if the program is run on an unsupported processor, an invalid instruction fault may occur. Note that this may change floating point results since the Intel® SSE instructions will be used instead of the x87 instructions and therefore computations will be done in the declared precision rather than sometimes a higher precision.

All Intel® 64 architecture processors support Intel® SSE2.

To specify the older default of generic IA-32, specify `-mia32`

3.4.4 OpenMP* Libraries Default to “compat”

In version 10.1, a new set of OpenMP libraries was added that allowed applications to use OpenMP* code from both Intel and Microsoft compilers. These “compatibility” libraries can provide higher performance than the older “legacy” libraries. In version 11.x, the compatibility libraries are used by default for OpenMP applications, equivalent to `-openmp-lib compat`. If you wish to use the older libraries, specify `-openmp-lib legacy`

The “legacy” libraries will be removed in a future release of the Intel compilers.

3.4.5 `mathf.h` No Longer Provided

The header file `mathf.h`, used to define single-precision math library functions, has been removed from the product. If you were using this header file, please use `mathimf.h` instead.

3.4.6 Sampling-based Profile Guided Optimization Feature Removed

The hardware sampling-based Profile-Guided Optimization feature is no longer provided. The `-prof-gen-sampling` and `-ssp` compiler options and the `profrun` and `pronto_tool` executables have been removed. Instrumented Profile-Guided Optimization is still supported.

3.4.7 OpenMP Header File Changed

The OpenMP header file `omp.h` has been improved with additional error checking in version 11.1 Update 4.

The definitions of `omp_lock_t` and `omp_nest_lock_t` types have changed. With this release, the compiler distinguishes these types at compile time. This change will not affect OpenMP programs written in conformance with the OpenMP specification. However, a non-conforming OpenMP application may generate a compiler warning. For example:

```
$ cat sample.c
#include <omp.h>
int main() {
    omp_lock_t lk;
    omp_init_nest_lock( & lk );
    return 0;
} // main

$ icc -openmp sample.c

sample.c(4): warning #167: argument of type "omp_lock_t *" is
incompatible with parameter of type "omp_nest_lock_t *"

    omp_init_nest_lock( & lk );
                        ^
```

3.5 Using Source Checker in the Eclipse* IDE

When Source Checker (formerly Static Verifier) support is enabled within the IDE, the customary final build target (e.g. an executable image) is not created. As such, we recommend that a separate "Source Checking" configuration be created, by cloning the existing Debug (development) configuration, for use when static verification is desired.

- Open the property pages for the project and select "C/C++ Build".
- Click the "Manage" button
- In the "Manage" dialog, click the "New" button to open the "Create configuration" dialog.
- Supply a name for the new configuration in the "Name" box.
- Supply a "Description" for the configuration if you want (optional).
- You can choose to "Copy settings from" a "Default configuration" or an "Existing configuration" by clicking the appropriate radio button and then selecting a configuration from the corresponding drop down menu.
- Click "O.K." to close the "Create configuration" dialog.
- Click "O.K." to close the "Manage" dialog (with your new configuration name selected).
- The property pages will now be displaying the settings for your new configuration and it is now the active build configuration.
- Navigate to the Intel compiler's Compilation Diagnostics properties. Use the "Level of Source Code Analysis", "Level of Source Code Parallelization Analysis" and "Analyze Included Files" properties to control source code analysis.

3.6 Known Issues

3.6.1 TR1 System Headers

If you are using the TR1 (C++ Library Technical Report 1) system headers on a system with g++ version 4.3 or later installed, the Intel C/C++ compiler will give errors when it tries to compile the <type_traits> header file. This is because the Intel C/C++ compiler does not yet support the C++0x feature called variadic templates. You will see these types of compilation errors:

```
../include/c++/4.3.0/tr1_impl/type_traits(170): error: expected an
identifier
    template<typename _Res, typename... _ArgTypes>
        ^
include/c++/4.3.0/tr1_impl/type_traits(171): error: expected a ")"
    struct __is_function_helper<_Res(_ArgTypes...)>
```

There is no workaround, other than not using these headers or using an older version of the g++ compiler.

3.6.2 The default behavior for `KMP_AFFINITY` has changed

The thread affinity type of the `KMP_AFFINITY` environment variable defaults to none (`KMP_AFFINITY=none`). The behavior for `KMP_AFFINITY=none` was changed in 10.1.015 or later, and in all 11.x compilers, such that the initialization thread creates a "full mask" of all the threads on the machine, and every thread binds to this mask at startup time. It was subsequently found that this change may interfere with other platform affinity mechanisms, for example, `dplace()` on SGI Altix machines. To resolve this issue, a new affinity type disabled was introduced in compiler 10.1.018, and in all 11.1 compilers (`KMP_AFFINITY=disabled`). Setting `KMP_AFFINITY=disabled` will prevent the OpenMP runtime library from making any affinity-related system calls.

3.6.3 Fatal error from old version of ld

In some circumstances, linking of an application with the version 11.x compiler will fail with an ld internal error similar to the following:

```
ld: BFD 2.15.92.0.2 20040927 internal error, aborting at
../bfd/reloc.c line 444 in bfd_get_reloc_size
ld: Please report this bug.
```

To resolve this, install a more recent version of binutils. 2.17.50 is the recommended minimum version.

3.6.4 Certain Intel® AVX Architecture Instructions and Intrinsics Removed

The compiler does not support the `VPERMIL2PD` and `VPERMIL2PS` instructions in the assembler, and does not support the corresponding intrinsics `_mm256_permute2_pd`, `_mm_permute2_pd`, `_mm256_permute2_ps`, and `_mm_permute2_ps`. These instructions and

intrinsics were removed from the Intel® AVX architecture but not from the compiler documentation. For more information, please see <http://software.intel.com/en-us/blogs/2009/01/29/recent-intelr-avx-architectural-changes/>

4 Intel® Debugger (IDB)

The following notes refer to the Graphical User Interface (GUI) available for the Intel® Debugger (IDB) when running on IA-32 and Intel® 64 architecture systems. In this version, the `idb` command invokes the GUI – to get the command-line interface, use `idbc`.

On IA-64 architecture systems, the GUI is not available and the `idb` command invokes the command-line interface.

4.1 Setting up the Java Runtime Environment

The Intel® IDB Debugger graphical environment is a Java application and requires a Java Runtime Environment (JRE) to execute. The debugger will run with a version 5.0 (also called 1.5) or 6.0 (1.6) JRE.

Install the JRE according to the JRE provider's instructions.

Finally you need to export the path to the JRE as follows:

```
export PATH=<path_to_JRE_bin_dir>:$PATH
```

4.2 Starting the Debugger

To start the debugger, first make sure that the compiler environment has been established as described at [Establishing the Compiler Environment](#). Then use the command:

```
idb
```

or

```
idbc
```

as desired.

Once the GUI is started and you see the console window, you're ready to start the debugging session.

Note: Make sure that the executable you want to debug is built with debug info and is an executable file. Change permissions if required, e.g. `chmod +x <application_bin_file>`

4.3 Additional Documentation

Online help titled *Intel® Compilers / Intel® Debugger Online Help* is accessible from the debugger graphical user interface as `Help > Help Contents`.

Context-sensitive help is also available in several debugger dialogs where a `Help` button is displayed.

4.4 Debugger Features

4.4.1 Main Features of IDB

The debugger supports all features of the command line version of the Intel® IDB Debugger. Debugger functions can be called from within the debugger GUI or the GUI-command line. Please refer to the Known Limitations when using the graphical environment.

4.4.2 New and Changed Features

- Debugger GUI for IA-32 and Intel® 64 architectures
- Parallel Execution Debug Support
- Session Concept
- Bitfield editor
- SIMD registers window
- OpenMP support
 - Information windows for Tasks, Barriers, Taskwaits, Locks, Teams and Task Spawn Tree
 - Data sharing events and reentrancy call detection
 - Debugging serialized code without recompilation
- Internationalization support

4.5 Known Problems

4.5.1 Data Sharing Detection Issues

- When the `Stop On Event` icon is deactivated, or the `Parallel > Stop on Event` menu item is unchecked, data sharing events are not collected in the Data Sharing Events window. If you stop the debugger and open the Data Sharing Events window, you will see only the last event.
- When the `Data Sharing Events` window is closed and reopened, a new Analysis Run Node will be displayed that duplicates recent events.
- When the `Data Sharing Events` window is closed during data sharing detection, only the last event is displayed when the window is reopened after detection.

4.5.2 Signals Dialog not working

The Signals dialog accessible via the GUI dialog `Debug / Signal Handling` or the shortcut `Ctrl+S` is not working correctly. Please refer to the Intel® Debugger (IDB) Manual for use of the signals command line commands instead.

4.5.3 Break on Re-entrant Call not Supported

The Break on Re-Entrant Call functionality is not supported with this debugger release. With the menu `Icon Break on Re-entrant Call...` or via menu item `Parallel > Break on Re-entrant Call...` you can set conditions, but the debugger will not issue any results of occurring re-entrant function calls.

4.5.4 Resizing GUI

If the debugger GUI window is reduced in size, some windows may fully disappear. Enlarge the window and the hidden windows will appear again.

4.5.5 Kill Process

The 'Kill Focused Process' command from the Debug menu does not work when the debugger is running. Stop the debugger first and then kill the process.

4.5.6 Decimal Floating Point Not Supported

The Intel® Debugger does not support decimal floating point data types, supported in some C++ compilers. The debugger will display such values as if they were arrays of characters.

4.5.7 \$cdir, \$cwd Directories

\$cdir is the compilation directory (if recorded). This is supported in that the directory is set; but \$cdir is not itself supported as a symbol.

\$cwd is the current working directory. Neither the semantics nor the symbol are supported.

The difference between \$cwd and '.' is that \$cwd tracks the current working directory as it changes during a debug session. '.' is immediately expanded to the current directory at the time an entry to the source path is added.

4.5.8 info stack Usage

The debugger command `info stack` does not currently support negative frame counts in the optional syntax below:

```
info stack [num]
```

A positive frame count `num` will print the innermost `num` frames. A negative or zero count will print no frames rather than the outermost `num` frames.

4.5.9 \$stepg0 Default Value Changed

The debugger variable `$stepg0` changed default to a value of 0. With the value "0" the debugger will step over code without debug information if you do a "step" command. Set the debugger variable to 1 to be compatible with previous debugger versions as follows:

```
(idb) set $stepg0 = 1
```

4.5.10 SIGTRAP error on some Linux* Systems

On some rare cases with special Linux kernels a SIGTRAP error may occur when the debugger stops at a breakpoint and you continue debugging. As a workaround you can define the SIGTRAP signal as follows on command line:

```
(idb) handle SIGTRAP nopass noprint nostop
SIGTRAP is used by the debugger.
SIGTRAP      No      No      No      Trace/breakpoint trap
(idb)
```

4.5.11 idb GUI cannot be used to debug MPI processes

The `idb` GUI cannot be used to debug MPI processes. The command line interface (`idbc`) can be used for this purpose.

5 Eclipse Integration

The Intel C++ Compiler for the IA-32 and Intel® 64 architectures installs an Eclipse feature and associated plugins (the Intel C++ Eclipse Product Extension) which provide support for the Intel C++ compiler when added as an Eclipse product extension site to an existing instance of the Eclipse* Integrated Development Environment (IDE). With this feature, you will be able to use the Intel C++ compiler from within the Eclipse integrated development environment to develop your applications.

5.1 Supplied Integrations

5.1.1 Eclipse 3.5 and CDT 6.0

The Intel feature provided in the directory

```
<install-dir>/eclipse_support/cdt6.0/eclipse
```

supports and requires Eclipse Platform version 3.5.x, Eclipse C/C++ Development Tools (CDT) version 6.0.0 or later and a functional Java Runtime Environment (JRE) (minimum version 5.0 (also called 1.5), recommended version 6.0).

5.1.2 Eclipse 3.4 and CDT 5.0

The Intel feature provided in the directory

```
<install-dir>/eclipse_support/cdt5.0/eclipse
```

supports and requires Eclipse Platform version 3.4.x, Eclipse C/C++ Development Tools (CDT) version 5.0.0 or later and a functional Java Runtime Environment (JRE) (minimum version 5.0 (also called 1.5), recommended version 6.0).

5.1.3 Integration notes

Note that the Eclipse Platform versions 3.5 and 3.4 are not currently available for the IA-64 architecture. The compiler kit includes an Eclipse integration for that architecture should the platform be released at a later date.

If you already have the proper versions of Eclipse, CDT and a functional JRE installed and configured in your environment, then you can add the Intel C++ Eclipse Product Extension to your Eclipse Platform, as described in the section, below, entitled [How to Install the Intel C++ Eclipse Product Extension in Your Eclipse Platform](#). Otherwise, you will first need to obtain and install Eclipse, CDT and a JRE, as described in the section, below, entitled [How to Obtain and Install Eclipse, CDT and a JRE](#) and then install the Intel C++ Eclipse Product Extension.

5.2 How to Install the Intel C++ Eclipse Product Extension in Your Eclipse Platform

To add the Intel C++ product extension to your existing Eclipse configuration, follow these steps, from within Eclipse.

5.2.1 Eclipse 3.5.0 and CDT 6.0.0 “Galileo”

Open the "Available Software" page by selecting: `Help > Install New Software...`
Click on the "Add..." button. Select "Local...". A directory browser will open. Browse to select the `eclipse` directory in your Intel C++ compiler installation. For example, if you installed the compiler as root to the default directory, you would browse to `/opt/intel/Compiler/11.1/uuu/eclipse_support/cdt6.0/eclipse`. Select "OK" to close the directory browser. Then select "OK" to close the "Add Site" dialog. Select the two boxes for the Intel C++ integration: there will be one box for "Intel® C++ Compiler Documentation" and a second box for "Intel® C++ Compiler Professional 11.1 for Linux*". **Note:** The Intel features will not be visible if you have `Group items by category` set – unset this option to view the Intel features.

Click the "Install" button. An "Install" dialog will open which gives you a chance to review and confirm you want to install the checked items. Click "Next". You will now be asked to accept the license agreement. Accept the license agreement and click "Finish". The installation of the Intel support will proceed.

When asked to restart Eclipse, select "Yes". When Eclipse restarts, you will be able to create and work with CDT projects that use the Intel C++ compiler. See the Intel C++ Compiler documentation for more information. You can find the Intel C++ documentation under `Help > Help Contents > Intel C++ Compiler Users Guide`. If you also installed the Intel® Debugger (idb) along with the idb Eclipse product extension, and would like to use idb within Eclipse, you should add the idb product extension site to your Eclipse configuration in the same way. For example, if you installed the kit as root to the default directory, you would find the idb Eclipse product extension site at `/opt/intel/Compiler/11.1/uuu/idb/eclipse_support/cdt6.0/eclipse`.

5.2.2 Eclipse 3.4.0 and CDT 5.0.0 “Ganymede”

Open the "Software Updates and Add-ons" page by selecting:

`Help > Software Updates...`

Select the "Available Software" tab.

Select "Add Site..." and then "Local...". A directory browser will open. Browse to select the `eclipse` directory in your Intel C++ compiler installation. For example, if you installed the compiler as root to the default directory, you would browse to `/opt/intel/Compiler/11.1/uuu/eclipse_support/cdt5.0/eclipse`.

Select "OK" to close the directory browser. Then select "OK" to close the "Add Site" dialog. Select the two boxes for the Intel C++ integration: there will be one box for "Intel® C++ Compiler Documentation" and a second box for "Intel® C++ Compiler 11.1 for Linux*". **Note:** The Intel features will not be visible if you have `Group items by category` set – unset this option to view the Intel features.

Click the “Install” button. An “Install” dialog will open which gives you a chance to review and confirm you want to install the checked items. Click “Next”. You will now be asked to accept the license agreement. Accept the license agreement and click “Finish”. The installation of the Intel support will proceed.

When asked to restart Eclipse, select “Yes”. When Eclipse restarts, you will be able to create and work with CDT projects that use the Intel C++ compiler. See the Intel C++ Compiler documentation for more information. You can find the Intel C++ documentation under `Help > Help Contents > Intel C++ Compiler User and Reference Guides`.

If you also installed the Intel® Debugger (idb) along with the idb Eclipse product extension, and would like to use idb within Eclipse, you should add the idb product extension site to your Eclipse configuration in the same way. For example, if you installed the kit as root to the default directory, you would find the idb Eclipse product extension site at `/opt/intel/Compiler/11.1/uuu/idb/eclipse_support/cdt5.0/eclipse`.

5.3 How to Obtain and Install Eclipse, CDT and a JRE

Eclipse is a Java application and therefore requires a Java Runtime Environment (JRE) to execute. The 3.4.0 version of the Eclipse platform will run with a minimum version 5.0 JRE. Intel recommends using a 6.0 (1.6) JRE. The choice of a JRE is dependent on your operating environment (machine architecture, operating system, etc.) and there are many JRE's available to choose from.

5.3.1 Eclipse 3.5.0 with CDT 6.0.0

A package containing both Eclipse 3.5.0 and CDT 6.0.0 is available from:

`http://www.eclipse.org/downloads/packages/eclipse-ide-cc-developers/galileor`

Choose either the Linux 32bit or Linux 64bit download as desired.

5.3.2 Eclipse 3.4.0 and CDT 5.0.0

A package containing both Eclipse 3.4.0 and CDT 5.0.0 is available from:

`http://www.eclipse.org/downloads/packages/release/ganymede/r`

Find “Eclipse IDE for C/C++ Developers” and choose either the Linux 32bit or Linux 64bit download as desired.

5.3.3 Installing JRE, Eclipse and CDT

Once you have downloaded the appropriate files for Eclipse, CDT, and a JRE, you can install them as follows:

1. Install your chosen JRE according to the JRE provider's instructions.
2. Create a directory where you would like to install Eclipse and `cd` to this directory. This directory will be referred to as `<eclipse-install-dir>`
3. Copy the Eclipse package binary `.tgz` file to the `<eclipse-install-dir>` directory.

4. Expand the `.tgz` file.
5. Start `eclipse`

You are now ready to add the Intel C++ product extension to your Eclipse configuration as described in the section, *How to Install the Intel C++ Eclipse Product Extension in Your Eclipse Platform*. If you need help with launching Eclipse for the first time, please read the next section.

5.4 Launching Eclipse for Development with the Intel C++ Compiler

If you have not already set your `LANG` environment variable, you will need to do so. For example,

```
setenv LANG en_US
```

Setup Intel C++ compiler related environment variables by executing the `iccvars.csh` (or `.sh`) script prior to starting Eclipse:

```
source <install-dir>/bin/iccvars.csh arch_arg (where "arch_arg" is one of "ia32" or "intel64").
```

Since Eclipse requires a JRE to execute, you must ensure that an appropriate JRE is available to Eclipse prior to its invocation. You can set the `PATH` environment variable to the full path of the folder of the `java` file from the JRE installed on your system or reference the full path of the `java` executable from the JRE installed on your system in the `-vm` parameter of the Eclipse command, e.g.:

```
eclipse -vm /JRE folder/bin/java
```

Invoke the Eclipse executable directly from the directory where it has been installed. For example:

```
<eclipse-install-dir>/eclipse/eclipse
```

5.5 Installing on Fedora* Systems

If the Intel C++ Compiler for Linux is installed on an IA-32 or Intel® 64 architecture Fedora* system as a "local" installation, i.e. not installed as root, the installation may fail to properly execute the Eclipse graphical user interfaces to the compiler or debugger. The failure mechanism will typically be displayed as a `JVM Terminated` error. The error condition can also occur if the software is installed from the root account at the system level, but executed by less privileged user accounts.

The cause for this failure is that a more granular level of security has been implemented on Fedora, but this new security capability can adversely affect access to system resources, such as dynamic libraries. This new *SELinux* security capability may require adjustment by your system administrator in order for the compiler installation to work for regular users.

5.6 Selecting Compiler Versions

For Eclipse projects you can select among the installed versions of the Intel C++ Compiler. On IA-32 architecture systems, the supported Intel compiler versions are 9.1, 10.0, 10.1, 11.0 and 11.1. On Intel® 64 architecture systems, only compiler versions 11.0 and 11.1 are supported.

6 Intel® Integrated Performance Primitives

This section summarizes changes, new features and late-breaking news about the Intel® Integrated Performance Primitives (Intel® IPP) as part of Intel C++ Compiler Professional Edition. For detailed information about Intel® IPP see the following links:

- **New features:** see the information below and visit the main Intel IPP product page on the Intel web site at: <http://software.intel.com/en-us/intel-ipp>.
- **Documentation, help, and samples:** see the documentation links on the IPP product page at: <http://software.intel.com/en-us/intel-ipp>.

6.1 New and Changed Features

6.1.1 Intel® Integrated Performance Primitives 6.1 Update 5

- This release contains no new features, only corrections to reported problems

6.1.2 Intel® Integrated Performance Primitives 6.1 Update 4

- New string processing code examples in the IPP signal processing reference manual.
- Optimizations for RSA-1024 based decryption added to the library.
- OpenSSL performance improvements and support for version 0.9.8j of OpenSSL.

6.1.3 Intel® Integrated Performance Primitives 6.1 Update 3

- New code examples in chapter 11 of the IPP signal processing reference manual.
- UMC documentation now includes motion estimation and mode decision components.
- Approximate 5% performance improvement to the BZIP2 decoder.

6.1.4 Intel® Integrated Performance Primitives 6.1 Update 2

- Support Intel® Advanced Vector Extensions (Intel® AVX)
- Support Intel® Core™ i7 processor with new optimization and threading control/optimization
- 3D Image Processing: 3D Geometric Transforms, 3D Filters
- New Data Compression Functions APIs
- New Intel IPP Crypto support to RSA_SSA1.5 and RSA_PKCSv1.5
- Unified Image Classes (UIC) to add PNG format support and new features to support DXT1, DXT3, DXT5 texture compression
- Advanced lighting functions including Spherical Harmonic and Perlin Noise generation Functions
- Windows Media* Photo Support (HD Photo): IPP PCT Functions

- New video coding areas improvement including Scene Analyzer in MPEG-2, Intensity Compensation & Overlap Smoothing in VC1
- Samples for Signal Processing, Image Processing, String Processing and C++, C# language support have been added in /Samples folder. Others can be downloadable by clicking “Free Code Samples” at <http://software.intel.com/en-us/intel-ipp>
- The deprecated APIs have been added more reference information in reference manual and header files.

6.2 Known Limitations

- For a list of bug fixes, known issues, and limitations please see the following knowledge base article: <http://software.intel.com/en-us/articles/intel-ipp-library-61-fixes-list/>.

6.3 Intel® IPP Cryptography Libraries are Available as a Separate Download

The Intel® IPP cryptography libraries are available as a separate download. For download and installation instructions, please read

<http://software.intel.com/en-us/articles/download-ipp-cryptography-libraries/>

6.4 Intel® IPP Code Samples

The Intel® IPP code samples are organized into downloadable packages for Windows*, Linux* and Mac OS* at

<http://software.intel.com/en-us/articles/intel-integrated-performance-primitives-code-samples/>

The samples include source code for audio/video codecs, image processing and media player applications, and for calling functions from C++, C# and Java*. Instructions on how to build the sample are described in a readme file that comes with the installation package for each sample.

7 Intel® Math Kernel Library

This section summarizes changes, new features and late-breaking news about the Intel® Math Kernel Library (Intel® MKL) as part of Intel C++ Compiler Professional Edition.

7.1 Changes in This Version

For further information on improvements in this and previous releases, see

<http://software.intel.com/en-us/articles/new-in-intel-mkl-10-2/>.

For bug fixes see the list at <http://software.intel.com/en-us/articles/intel-mkl-102-fixes-list/>.

7.1.1 Intel® Math Kernel Library 10.2 Update 6

New Features

- Integrated Netlib LAPACK 3.2.2 including one new computational routine (?GEQRF) and two new auxiliary routines (?GEQR2P and ?LARFGP)

Performance Improvements

- Improved DZGEMM performance on Intel® Xeon® processors series 5300 and 5400 with 64-bit operating systems
- Improved DSYRK performance on Intel® Xeon® processors series 5300 with 32-bit operating systems with the most significant improvements for small oblong matrices on 8 and more threads
- Improved the scalability of (C/Z)GGEV by parallelizing the reduction to generalized Hessenberg form ((C/Z)GGHRD)
- Improved performance for (SY/HE)EV and (SP/HP)TRS on very small matrices (< 20)
- Improved performance of FFTW2 wrappers for those cases where the descriptor remains constant from call to call
- Improved Scalability of threaded applications that use non-threaded FFTs on multi-socket systems
- Significantly improved performance of cluster FFTs through better load balancing when the input data cannot be evenly distributed between MPI processes
- Improved scalability of cluster FFTs on systems with a non-power-of-2 number of cores/processors
- Improved performance of factorization step in PARDISO out-of-core for huge matrices through reduction in the number of disk IO operations
- Parallelized solve step in PARDISO

Usability/Interface improvements

- Improved support for F77 in FFTW2 and MPI FFTW2 interfaces
- Implemented rfftwnd_create_plan_specific and its 2d and 3d variants
- Added 2D Convolution/Correlation examples

7.1.2 Intel® Math Kernel Library 10.2 Update 5

New Features

- Incorporated the LAPACK 3.2.1 update primarily consisting of fixes to LAPACK 3.2

Performance Improvements

- FFTs
 - Improved performance for complex FFTs, 3D and higher on the Intel® 64 architecture
- VSL
 - Improved performance of the MT19937 and MT2203 basic random number generators (BRNGs) on the 45nm Intel® Core™2 Duo processor and newer processors in 64-bit libraries

Usability and Interface Improvements

- Added support for Boost version 1.41.0 in the ublas examples
- Included Fortran 95 interfaces for the diagonally dominant solver functionality (?DTSVB, ?DTTRFB, ?DTTRSB)
- Significantly reduced the memory consumption of in-place, multi-dimensional cluster FFTs

7.1.3 Intel® Math Kernel Library 10.2 Update 4

New Features

- Introduced the single precision complex absolute value function SCABS1
- Introduced the solver ?DTSVB for diagonally dominant tri-diagonal systems which is up to 2x faster than the general solver with partial pivoting (?GTSV)
- Added routines for factorization (?DTTRFB) and the forward/backward substitution (?DTTRSB) of the diagonally dominant tri-diagonal systems

Performance improvements

- FFTs
 - Enhanced performance for transforms which are a multiple of 8 or 13
 - Optimized 1D complex cluster FFTs for non-power-of-2 vector lengths
- VSL
 - Convolution and Correlation computations that require decimation show significant improvements (re-link required, see [Known Issues](#))

7.1.4 Intel® Math Kernel Library 10.2 Update 3

Performance Improvements

- BLAS
 - Threaded the 32-bit OS versions of the following BLAS Level 1 and 2 functions for Intel® Core™ i7 processors and Intel® Xeon® processor 5300, 5400, and 5500 series: (D,S,C,Z)COPY, (D,S,C,Z)SWAP, (D,S,C,Z)AXPY, (S,C)ROT, (S,C)DOT, CDOTC, (D,S,C,Z)GEMV, (D,S,C,Z)TRMV, (S,C)SYMV, (S,C)SYR, (S,C)SYR2
 - Improved 32-bit and 64-bit OS versions of the following BLAS level 1 functions for Intel® Xeon® processors 5300, 5400, 5500: ZAXPY, ZSCAL, ZDOT(U,C), and (D,S)ROT
 - Improved DGEMM threading efficiency for matrices with many more rows than columns for Intel® Xeon® processor 5300
- LAPACK
 - Improved scalability of the following LAPACK functions: ?POTRF, ?GEBRD, ?SYTRD, ?HETRD, and ?STEDC divide and conquer eigensolvers
- FFTs

- Updated underlying kernels to provide widespread performance improvements in FFTs
- Improved threading of 3D FFTs when a small number of transforms are calculated with a single function call
- Extended threading to small size multidimensional transforms
- VML
 - Further optimization for these VML functions on Intel® Xeon® processor 5500 series: v(s,d)Asin, v(s,d)Acos, v(s,d)Ln, v(s,d)Log10, vsLog1p, v[s/d]Hypot
- VSL
 - Improved performance of viRngPoisson and viRngPoissonV random number generators

Usability and Interface Improvements

- Improved example programs for uBLAS, Java, FFTW3, LAPACK95, and BLAS95
- Some examples in the reference manual were removed where identical examples in source code form also appeared in the examples directory
- New 64-bit integer (ILP64) fftw_mpi interfaces for cluster FFTs

7.1.5 Intel® Math Kernel Library 10.2 Update 2

New Features

- LAPACK 3.2
 - 238 new LAPACK functions
 - Extra Precise Iterative Refinement
 - Non-Negative Diagonals from Householder QR factorization
 - High Performance QR and Householder Reflections on Low-Profile Matrices
 - New fast and accurate Jacobi SVD
 - Routines for Rectangular Full Packed format
 - Pivoted Cholesky
 - Mixed precision iterative refinement (Cholesky)
 - More robust DQDS algorithm
- Introduced implementation of the DZGEMM Extended BLAS function (as described at <http://www.netlib.org/blas/blast-forum/>). See the description of the *gemm family of functions in the BLAS section of the reference manual.
- PARDISO now supports real and complex, single precision data

Usability/Interface improvements

- Sparse matrix format conversion routines which convert between the following formats:
 - CSR (3-array variation) ↔ CSC (3-array variation)
 - CSR (3-array variation) ↔ diagonal format

- CSR (3-array variation) ↔ skyline
- Fortran95 BLAS and LAPACK compiled module files (.mod) are now included
 - Modules are pre-built with the Intel Fortran Compiler and are located in the include directory (see Intel® MKL User's Guide for full path)
 - Source is still available for use with other compilers
 - Documentation for these interfaces can be found in the Intel® MKL User's Guide
- The FFTW3 interface is now integrated directly into the main libraries
 - Source code is still available to create wrappers for use with compilers not compatible with the default Intel® Fortran compiler convention for name decoration
 - See Appendix G of the Reference Manual for information
- DFTI_DESCRIPTOR_HANDLE now represents a true type name and can now be referenced as a type in user programs
- Added parameter to Jacobi matrix calculation routine in the optimization solver domain to allow access to user data (see the description of the djacobix function in the reference manual for more information)
- Added an interface mapping calls to single precision BLAS functions in Intel® MKL (functions with "s" or "c" initial letter) to 64-bit floating point precision functions has been added on 64-bit architectures (See "sp2dp" in the Intel® MKL User Guide for more information)
- Compatibility libraries (also known as "dummy" libraries) have been removed from this version of the library

Performance improvements

- Further threading in BLAS level 1 and 2 functions for Intel® 64 architecture
 - Level 1 functions (vector-vector): (C,S,Z,D)ROT, (C,Z,S,D)COPY, and (C,Z,S,D)SWAP
 - Increase in performance by up to 1.7-4.7 times over version 10.1 Update 1 on 4-core Intel® Core™ i7 processor depending on data location in cache
 - Increase in performance by up to 14-130 times over version 10.1 Update 1 on 24-core Intel® Xeon® processor 7400 series system, depending on data location in cache
 - Level 2 functions (matrix-vector): (C,Z,S,D)TRMV, (S,D)SYMV, (S,D)SYR, and (S,D)SYR2
 - Increase in performance by up to 1.9-2.9 times over version 10.1 Update 1 on 4-core Intel® Core™ i7 processor, depending on data location in cache
 - Increase in performance by up to 16-40 times over version 10.1 Update 1 on 24-core Intel® Xeon® processor 7400 series system, depending on data location in cache

- Introduced recursive algorithm in 32-bit sequential version of DSYRK for up to 20% performance improvement on Intel® Core™ i7 processors and Intel® Xeon® processors in 5300, 5400, and 7400 series.
- Improved LU factorization (DGETRF) by 25% over Intel MKL 10.1 Update 1 for large sizes on the Intel® Xeon® 7460 Processor; small sizes are also dramatically improved
- BLAS *TBMV/*TBSV functions now use level 1 BLAS functions to improve performance by up to 3% on Intel® Core™ i7 processors and up to 10% on Intel® Core™2 processor 5300 and 5400 series.
- Improved threading algorithms to increase DGEMM performance
 - up to 7% improvement on 8 threads and up to 50% on 3,5,7 threads on the Intel® Core™ i7 processor
 - up to 50% improvement on 3 threads on Intel® Xeon® processor 7400 series.
- Threaded 1D complex-to-complex FFTs for non-prime sizes
- New algorithms for 3D complex-to-complex transforms deliver better performance for small sizes (up to 64x64x64) on 1 or 2 threads
- Implemented high-level parallelization of out-of-core (OOC) PARDISO when operating on symmetric positive definite matrices.
- Reduced memory use by PARDISO for both in-core and out-of-core on all matrix types
- PARDISO OOC now uses less than half the memory previously used in Intel MKL 10.1 for real symmetric, complex Hermitian, or complex symmetric matrices
- Parallelized Reordering and Symbolic factorization stage in PARDISO/DSS
- Up to 2 times better performance (30% improvement on average) on Intel® Core® i7 and Intel® Core™2 processors for the following VML functions: $v(s,d)Round$, $v(s,d)Inv$, $v(s,d)Div$, $v(s,d)Sqrt$, $v(s,d)Exp$, $v(s,d)Ln$, $v(s,d)Atan$, $v(s,d)Atan2$
- Optimized versions of the following functions available for Intel® Advanced Vector Extensions (Intel® AVX)
 - BLAS: DGEMM
 - FFTs
 - VML: exp, log, and pow
 - See important information in the Intel® MKL User's Guide regarding the `mkl_enable_instructions()` function for access to these functions

7.2 Known Issues

A full list of the known limitations of this release can be found in the Knowledge Base for the Intel® MKL at <http://software.intel.com/en-us/articles/known-limitations-in-intel-mkl-10-2>

7.3 Notices

The following change is planned for future versions of Intel® MKL. Please contact [Technical Support](#) if you have concerns:

- Content in the libraries containing `solver` in the filenames will be moved to the core library in a future version of Intel® MKL. These `solver` libraries will then be removed.

7.4 Attributions

As referenced in the End User License Agreement, attribution requires, at a minimum, prominently displaying the full Intel product name (e.g. "Intel® Math Kernel Library") and providing a link/URL to the Intel® MKL homepage (www.intel.com/software/products/mkl) in both the product documentation and website.

The original versions of the BLAS from which that part of Intel® MKL was derived can be obtained from <http://www.netlib.org/blas/index.html>.

The original versions of LAPACK from which that part of Intel® MKL was derived can be obtained from <http://www.netlib.org/lapack/index.html>. The authors of LAPACK are E. Anderson, Z. Bai, C. Bischof, S. Blackford, J. Demmel, J. Dongarra, J. Du Croz, A. Greenbaum, S. Hammarling, A. McKenney, and D. Sorensen. Our FORTRAN 90/95 interfaces to LAPACK are similar to those in the LAPACK95 package at <http://www.netlib.org/lapack95/index.html>. All interfaces are provided for pure procedures.

The original versions of ScaLAPACK from which that part of Intel® MKL was derived can be obtained from <http://www.netlib.org/scalapack/index.html>. The authors of ScaLAPACK are L. S. Blackford, J. Choi, A. Cleary, E. D'Azevedo, J. Demmel, I. Dhillon, J. Dongarra, S. Hammarling, G. Henry, A. Petitet, K. Stanley, D. Walker, and R. C. Whaley.

PARDISO in Intel® MKL is compliant with the 3.2 release of PARDISO that is freely distributed by the University of Basel. It can be obtained at <http://www.pardiso-project.org>.

Some FFT functions in this release of Intel® MKL have been generated by the SPIRAL software generation system (<http://www.spiral.net/>) under license from Carnegie Mellon University. Some FFT functions in this release of the Intel® MKL DFTI have been generated by the UHFFT software generation system under license from University of Houston. The Authors of SPIRAL are Markus Puschel, Jose Moura, Jeremy Johnson, David Padua, Manuela Veloso, Bryan Singer, Jianxin Xiong, Franz Franchetti, Aca Gacic, Yevgen Voronenko, Kang Chen, Robert W. Johnson, and Nick Rizzolo.

8 Intel® Threading Building Blocks

This section summarizes changes, new features and late-breaking news about Intel® Threading Building Blocks (Intel® TBB) 2.2 as part of Intel® C++ Compiler Professional Edition.

8.1 Changes in This Version

8.1.1 Intel® Threading Building Blocks 2.2 Update 2

- `parallel_invoke` and `parallel_for_each` now take function objects by const reference, not by value.
- Improvements in exception support: new exception classes introduced, all exceptions are thrown via an out-of-line internal method.
- Improvements and fixes in the TBB allocator and malloc replacement, including robust memory identification, and more reliable dynamic function substitution on Windows*.

- Method `swap()` added to class `tbb_thread`.
- Methods `rehash()` and `bucket_count()` added to `concurrent_hash_map`.
- Other fixes and improvements in code, tests, examples, and docs.

8.1.2 Intel® Threading Building Blocks 2.2 Update 1

- Documentation was updated.
- TBB scheduler auto-initialization now covers all possible use cases.
- `concurrent_queue`: made argument types of `sizeof` used in padding consistent with those actually used.
- Memory allocator was improved: supported corner case of user's `malloc` calling `scalable_malloc` (non-Windows), corrected processing of memory allocation requests during `tbb` memory allocator startup (Linux).
- Windows `malloc` replacement has got better support for static objects.
- In pipeline setups that do not allow actual parallelism, execution by a single thread is guaranteed, idle spinning eliminated, and performance improved.
- RML refactoring and clean-up.
- New constructor for `concurrent_hash_map` allows reserving space for a number of items.
- Operator `delete()` added to the TBB exception classes.
- Lambda support was improved in `parallel_reduce`.
- gcc 4.3 warnings were fixed for `concurrent_queue`.
- Fixed possible initialization deadlock in modules using TBB entities during construction of global static objects.
- Copy constructor in `concurrent_hash_map` was fixed.
- Fixed a couple of rare crashes in the scheduler possible before in very specific use cases.
- Fixed a rare crash in the TBB allocator running out of memory.
- New tests were implemented, including `test_lambda.cpp` that checks support for lambda expressions.
- Fixed known exception safety issues in `concurrent_vector`.
- Better concurrency of simultaneous `grow` requests in `concurrent_vector`.
- TBB allocator further improves performance of large object allocation.
- Problem with source of text relocations was fixed on Linux
- Fixed bugs related to `malloc` replacement under Windows
- A few other small changes in code, tests, and documentation.

8.2 Known Issues

Please note the following with respect to this particular release of Intel Threading Building Blocks.

- Unhandled exceptions in the user code executed in the context of TBB algorithms or containers may lead to segmentation faults when Intel(R) C++ Compiler 10.x is used with `glibc` 2.3.2, 2.3.3, or 2.3.4.

- To allow more accurate results to be obtained with Intel® Thread Checker or Intel® Thread Profiler, download the latest update releases of these products before using them with Intel® Threading Building Blocks.
- If you are using Intel® Threading Building Blocks and OpenMP* constructs mixed together in rapid succession in the same program, and you are using Intel compilers for your OpenMP* code, set KMP_BLOCKTIME to a small value (e.g., 20 milliseconds) to improve performance. This setting can also be made within your OpenMP* code via the `kmp_set_blocktime()` library call. See the compiler OpenMP* documentation for more details on KMP_BLOCKTIME and `kmp_set_blocktime()`.
- In general, non-debug ("release") builds of applications or examples should link against the non-debug versions of the Intel® Threading Building Blocks libraries, and debug builds should link against the debug versions of these libraries. See the Tutorial in the product documentation sub-directory for more details on debug vs. release libraries.
- When using Ubuntu* 7.04 in 64-bit mode, compilations can fail with error messages saying that "'::system' has not been declared". These failures can be worked around by removing `libpthread-dev` from the system. See the following link for more details: <https://bugs.launchpad.net/ubuntu/+source/gcc-4.1/+bug/77559>

9 Disclaimer and Legal Information

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH INTEL(R) PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN INTEL'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, INTEL ASSUMES NO LIABILITY WHATSOEVER, AND INTEL DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF INTEL PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. UNLESS OTHERWISE AGREED IN WRITING BY INTEL, THE INTEL PRODUCTS ARE NOT DESIGNED NOR INTENDED FOR ANY APPLICATION IN WHICH THE FAILURE OF THE INTEL PRODUCT COULD CREATE A SITUATION WHERE PERSONAL INJURY OR DEATH MAY OCCUR.

Intel may make changes to specifications and product descriptions at any time, without notice. Designers must not rely on the absence or characteristics of any features or instructions marked "reserved" or "undefined." Intel reserves these for future definition and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to them. The information here is subject to change without notice. Do not finalize a design with this information.

The products described in this document may contain design defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request.

Contact your local Intel sales office or your distributor to obtain the latest specifications and before placing your product order.

Copies of documents which have an order number and are referenced in this document, or other Intel literature, may be obtained by calling 1-800-548-4725, or by visiting Intel's Web Site.

Parts of this product were built using third party libraries. Pursuant to the licenses ruling these libraries, Intel makes them available to users of this product. The libraries can be downloaded from Intel Software Development Products Knowledge Base article <http://software.intel.com/en-us/articles/open-source-downloads/> . Please note that download of these libraries is not required to use the product.

MPEG-1, MPEG-2, MPEG-4, H.263, H.264, MP3, DV SD/25/50/100, VC-1, G.722.1, G.723.1A, G.726, G.728, G.729, GSM/AMR, GSM/FR, JPEG, JPEG 2000, Aurora, TwinVQ, AC3 and AAC are international standards promoted by ISO, IEC, ITU, SMPTE, ETSI and other organizations. Implementations of these standards or the standard enabled platforms may require licenses from various entities, including Intel Corporation.

Celeron, Centrino, Intel, Intel logo, Intel386, Intel486, Intel Atom, Intel Core, Itanium, MMX, Pentium, VTune, and Xeon are trademarks of Intel Corporation in the U.S. and other countries.

* Other names and brands may be claimed as the property of others.

Copyright © 2010 Intel Corporation. All Rights Reserved.